

# DesignLights Consortium



Classification	Premium
Primary Use	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires
Reported Input Wattage	30 W
Reported Light Output	4530 lm
Reported CCT	3000 K
Reported CRI (Ra)	70
Product ID	S-0XBOTR
DLC Family Code	<a href="#">UUUVFU</a>
Listing Status	Listed
Date Qualified	2023-03-03

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-0XBOTR
Manufacturer	BIG SHINE LED
Brand	Big Shine LED
Model Number	BSL-PT30-PT7-WPSL-CCT03-V
Parent	Yes
Classification	Premium
DLC Family Code	UUUVFU
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Low Output
Primary Use Designation	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires

## PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Exterior Photocell
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4530 lm
Reported Efficacy (AC)	151 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	70
Reported R9	-36
Reported IES Rf	73
Reported IES Rg	93
Reported IES Rcs,h1	-17
Reported Minimum Light Output	1515 lm
Reported Maximum Light Output	4530 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	4530 lm
Reported BUG Rating	B2 U1 G1

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	30 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.95
Reported Minimum Input Wattage	9.9 W
Reported Maximum Input Wattage	30
Reported Default Input Wattage	30 W
Voltage Range	100-277 V

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	4936 lm
Tested Efficacy (AC)	152.2 lm/W
Tested CCT	3014 K
Tested CRI (Ra)	72
Tested R9	-36
Tested IES Rf	75
Tested IES Rg	93
Tested IES Rcs,h1	-17 %
Tested Duv	0.00113
Tested Backlight (TM-15 BUG)	2
Tested BUG Rating	B2 U1 G1

### TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	32.4 W
Tested Total Harmonic Distortion	9.1 %
Tested Power Factor	0.954

### VERSION HISTORY VIEW DETAILS

2023-03-03	Listed	5.1	Premium
------------	--------	-----	---------