DesignLights Consortium





Classification	Premium
Primary Use	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires
Reported Input Wattage	75 W
Reported Light Output	11475 lm
Reported CCT	4000 K
Reported CRI (Ra)	70
Product ID	S-DGO0FJ
DLC Family Code	UUUVGC
Listing Status	Listed
Date Qualified	2023-03-03

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-DGO0FJ
Manufacturer	BIG SHINE LED
Brand	Big Shine LED
Model Number	BSL-PT75-PT7-WPSL-CCT02-V
Parent	Yes
Classification	Premium
DLC Family Code	UUUVGC
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	High Output
Primary Use Designation	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires

PRODUCT CAPABILITIES VIEW DETAILS

1 of 3 3/8/2023, 2:37 PM

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	No Wired Communication Protocol
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	11475 lm
Reported Efficacy (AC)	153 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	70
Reported R9	-36
Reported IES Rf	73
Reported IES Rg	93
Reported IES Rcs,h1	-17
Reported Minimum Light Output	3443 lm
Reported Maximum Light Output	75 lm
Reported Minimum CCT	4000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	11475 lm
Reported BUG Rating	B2 U1 G1

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	75 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.95
Reported Minimum Input Wattage	22.5 W
Reported Maximum Input Wattage	75
Reported Default Input Wattage	75 W
Voltage Range	100-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

2 of 3 3/8/2023, 2:37 PM

Tested Light Output	11763 lm
Tested Efficacy (AC)	153 lm/W
Tested CCT	3998 K
Tested CRI (Ra)	75
Tested R9	-20
Tested IES Rf	75
Tested IES Rg	97
Tested IES Rcs,h1	-15 %
Tested Duv	-0.0019
Tested Backlight (TM-15 BUG)	3
Tested BUG Rating	B3 U2 G3

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	76.9 W
Tested Total Harmonic Distortion	12.7 %
Tested Power Factor	0.98

VERSION HISTORY VIEW DETAILS

3 of 3