




Description

The full cut-off LED wall pack uses advanced LED technology to provide bright, high-quality illumination while consuming minimal energy. It is often designed with durable, weather-resistant housing that can withstand harsh outdoor environments.

Applications


- Commercial Facilities
- Industrial Facilities

Photometry
100W

120W

Mounting Options

- Flush Mounting

Dimensions

100W-120W


Notes

*Power adjustable ranging from 25% to 100%

Electrical Information

Model No.	PXS-100	PXS-120
Power Consumption(±10%)	100W	120W
Power Supply	LED Driver	
Input Voltage	120-277V, 50/ 60Hz	
Power Factor	0.9	
Surge Protection	6kV L-N-PE, 4kV L-N	
Driver Type	Constant Current (CC)	
Control	0-10V Dimmable	

Optic Information

LED Type	SMD
Luminous Flux (±10%)	12,500 - 16,200 lm
Efficacy	125-135 lm/w
Correlated Color Temperature	3000K, 4000K, 5000K (Adjustable)
Color Rendering Index	Ra73
Beam Angle	90x110°
UGR level	<7

Dimensions and Mount

Export Carton Size	12.7" x 12.4" x 8.90"
Gross Weight	7.71 lbs
Mounting Option	Flush Mounting
Material	Die-Cast Aluminum Polycarbonate
Finish	Powder Coating
Fixture Color	Bronze, Black
IK Rating	N/A
IP Rating	IP65

Lifespan and Warranty

Operating Temperature	-40°F to 122°F
Warranty	5 Years

Safety Certifications

- Luminaires (UL 1598:2021 Ed.5)
- Luminaires (CSA C22.2#250.0:2021 Ed.5)