



DESCRIPTION




Introducing the AXS LED wall pack - the perfect solution for your outdoor lighting needs. With its adjustable power and CCT, you can customize your lighting experience to suit your preferences. The 100° beam angle ensures that your space is well-lit, providing optimal visibility and safety. The AXS LED wall pack boasts a sleek and modern design, featuring an aluminum body that is both durable and stylish. Its compact form factor makes it easy to install and unobtrusive, while still providing ample lighting coverage. With a CRI 80 rating, the AXS LED wall pack delivers true-to-life colors, enhancing the aesthetics of your space. Whether you're illuminating a commercial building, parking lot, or outdoor area, this wall pack is the perfect choice for any setting.

Wattage Adjustable: 25% or 100%

APPLICATIONS

- Commercial Facilities
- Industrial Facilities

PHOTOMETRY



MOUNTING OPTIONS

- Flush Mounting

Catalog Number	
Notes	
Type	

TECHNICAL SPECIFICATIONS

Model No.	AXS-15	AXS-20	AXS-30	
Power Consumption(±10%)	15W	20W	30W	
Power Supply	LED Driver			
Input Voltage	120-277V, 50/60Hz			
Power Factor	>0.9			
Surge Protection	2.5kV L-N, 2.5kV L-N-GND			
Driver Type	Constant Current (CC)			
Control	0-10V Dimmable			

OPTIC SPECIFICATIONS

LED Type	SMD			
Luminous Flux (±10%)	2024lm	2794lm	3933lm	
Efficacy (4000K Ra80)	135 lm/w	145 lm/w	135 lm/w	
Correlated Color Temperature	3000K, 4000K, 5000K (Adjustable)			
Color Rendering Index	Ra80			
Beam Angle	100°			
UGR level	<7			

MOUNTING AND PRODUCT DIMENSIONS

Product Dimension	8.6" x 5.7" x 3.1"
Luminaire Net Weight	N/A
Export Carton Size	6" x 3.5" x 8.8"
Gross Weight	2.9 lbs
Mounting Option	Flush Mounting
Material	Die-cast Aluminum Polycarbonate
Finish	Powder Coating
Fixture Color	Bronze, Black
IK Rating	N/A
IP Rating	IP65

LIFESPAN AND WARRANTY


Operating Temperature	-40°F to 113°F
Warranty	5 Years

SAFETY CERTIFICATIONS

- Luminaires (UL 1598:2021 Ed.5)
- Luminaires (CSA C22.2#250.0:2021 Ed.5)

DIMENSIONS (unit:mm)

15W-30W



ORDERING INFORMATION

AXS					
Series	Wattage & Lumen Output	Voltage	Correlated Color Temperature (CCT)	Beam Angle	Mounting Option
AXS (AXS LED Wall Pack)	15W (2024lm) 20W (2794lm) 30W (3933lm)	MV (120-277V)	30K (3000K) 40K (4000K) 50K (5000K)	100D (100°)	FM (Flush Mounting)
Mounting Option	Control Option	Accessories			
BK (Black) BZ (Bronze)	0-10V (0-10V Dimmable)	EMB (Battery Back-up)			